

Technical features

Armchair for conference halls, auditoriums and multi-purpose rooms.

Installation on flat and sloped floors or on steps, in straight or curved rows (minimum radius 8 m.).

Variable centre-to-centre distance from 53 to 60 cm.

Seat and backrest

Seat and backrest with plywood inner structure, fire-retardant and crushproof expanded polyurethane padding.

CertiPUR® certified padding. Wooden components with low formaldehyde emission.

Gravity tip-up seat with removable cover, equipped with steel rotation pins.

Seat and backrest fully with fabric, faux-leather or leather.

Sides

Fully padded sides with plywood internal structure, equipped with aluminium block for the insertion of rotation and seat support pins.

Wooden components with low formaldehyde emission.

Fabric, leather or faux-leather covering.

Right sides can be fitted with tip-up writing tablet in black stratified HPL and die-cast aluminum joint, that folds away into the side with anti-panic movement.

Floor fixing feet in steel profile painted with epoxy-polyester powder in RAL 9005 semi-matt, semi-matt silver, embossed bronze and embossed graphite scratchproof and anti-corrosion finishes.

Accessories

Tip-up writing table on single base mod T200.

Foldaway tip-up writing tablet with antipanic movement.

Seat numbering and row identification element.

Electric power supply provision (socket on demand).

Optional system allowing armchairs to be moved away on castors when unused (for straight row armchairs).

Tested according to European standards.