

Technical features

Armchair for conference halls, auditoriums, educational and multipurpose rooms.

Typologies

Armchair with inclined or straight floor-length sides, also available in increased width.

Installation on horizontal flooring, sloped flooring or on steps, in straight or curved rows (standard minimum radius 8 m.), 53 or 56 cm. centre to centre distance for the standard version and 56,58 or 60 cm. for the increased side version.

On project, L213 armchair can be installed with the innovative *Floor Technology* folding system, which rapidly drags the entire body of the seat in a horizontal position under the floor.

Seat and backrest

Seat and backrest with plywood internal structure and fire-retardant, non-deformable, shaped polyurethane foam padding.

Seat tilting with a gravity counterweight.

Visible plywood rear backrest with oak or beech finishes or completely upholstered and covered with fabric, faux-leather or leather.

In the rear part of the backrest, a folding table with anti-panic movement can be applied, equipped with slow and cushioned closing (Patent Pending) which guarantees a transition from the position of use to that of rest in a controlled, safe and silent manner.

CertiPUR® certified padding. Wooden components with low formaldehyde emission.

Sides

Inclined or straight bearing side with internal plywood structure equipped with metal inserts, available fully upholstered and covered with fabric, faux-leather or leather or in painted wood with oak or beech finishes. Wooden components with low formaldehyde emission.

The sides are also available in increased width.

Floor-anchor feet in moulded sheet metal covered with a protective scratchproof and anti-corrosion epoxy powder paint in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite finishes.

Side available with tip-up writing tablet in black stratified HPL and die-cast aluminum joint, that folds away into the side, with anti-panic movement.

Accessories

Tip-up writing table for the backrest with anti-panic movement, slow and cushioned closing (Patent Pending). Top in HPL laminate in beech, oak or black finishes.

Row identification element.

Seat numbering

Wood under seat panel with oak or beech finishes.

Stratified HPL tip-up foldaway writing tablet.
Electric power supply provision (socket on demand).
Painted wood backrest panel with oak or beech finishes.
Provision for audio/video devices (on project).
Tip-up writing tablet on single- base mod T200.

Tested according to European standards.