

# LAMM

## L213

R & D LAMM

### Technical features

Armchair for conference halls, auditoriums, educational and multipurpose rooms.

### Typologies

Armchair with inclined or straight floor-length sides, also available in increased width.

Installation on horizontal flooring, sloped flooring or on steps, in straight or curved rows (standard minimum radius 8 m.), 53 or 56 cm. centre to centre distance for the standard version and 56,58 or 60 cm. for the increased side version.

On project, L213 armchair can be installed with the innovative *Floor Technology* folding system, which rapidly drags the entire body of the seat in a horizontal position under the floor.

### Seat and backrest

Seat and backrest with plywood internal structure and fire-retardant, non-deformable, shaped polyurethane foam padding.

Seat tilting with a gravity counterweight.

Visible plywood rear backrest with oak, grey oak or eucalyptus finishes or completely upholstered and covered with fabric, eco-leather or leather.

### Sides

Inclined or straight bearing side with internal steel structure hidden into a MDF box, available fully upholstered and covered with fabric, eco-leather or leather or in painted wood with oak, grey oak or eucalyptus finishes.

The sides are also available in increased width.

Floor-fixing is hidden under a foot cover collar in pressed metal sheet in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite scratchproof epoxy powder paint.

Side available with stratified HPL writing tablet in black, with anti-panic, fold-away movement.

### Accessories

Tip-up writing tablet on single- base mod T200.

Backrest tip-up writing tablet with anti-panic movement, HPL bilaminate top with grey oak, eucalyptus or black finishes.

Row identification element.

Seat numbering (backrest application only).

Wood under seat panel with oak, grey oak or eucalyptus finishes.

Stratified HPL tip-up foldaway writing tablet.

Electric power supply provision (socket on demand).

Painted wood backrest panel with oak, grey oak or eucalyptus finishes.

Optional system allowing armchairs to be moved away (on wheels) in 2 or 3 seat units when unused (for floor-fixing armchairs in straight rows)

Provision for audio/video devices (on project).

Tested according to European standards.