

Technical features

Armchair for conference halls, auditoriums and multipurpose rooms.

Typologies

Armchairs with floor-length sides set up for floor fixing.

Available the version on beam of 2-3 places connected in rows.

Installation on flat and sloped floors or on steps, in straight or curved rows (armchairs with floor-length sides minimum radius 8m.).

Variable centre-to-centre distance from 53 to 60 cm.

Seat and backrest

Plywood internal structure, with flame-retardant, non-deformable, expanded polyurethane foam padding.

Backrest with steel internal side supports.

CertiPUR® certified padding. Wooden components with low formaldehyde emission.

Gravity tip-up seat, with rotation pins and steel support double plate.

Removable seat and backrest fully upholstered in fabric, faux-leather or leather.

Seat and backrest layout for stall and gallery inclination.

In the rear part of the backrest, a folding table with anti-panic movement can be applied, equipped with slow and cushioned closing (Patent Pending) which guarantees a transition from the position of use to that of rest in a controlled, safe and silent manner.

Sides

Bearing side with internal plywood structure equipped with metal inserts, available fully upholstered and covered in fabric, faux-leather or leather, or in wood painted in oak or beech finishes.

Wooden components with low formaldehyde emission.

Side provided with an aluminium block designed to insert the rotation and seat support pins.

Right sides can be fitted with foldaway tip-up writing tablet in black stratified HPL and aluminum die casting joint, that folds away into the side with anti-panic movement.

Floor-anchor feet in moulded sheet metal covered with a protective scratchproof and anti-corrosion epoxy powder paint in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite finishes.

Also available the beam version (2 or 3 places) in tubular steel rectangular section, painted with scratchproof and anti-corrosion epoxy powder paint in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite finish.

In the beam-mounted version, the sides have the same characteristics, but are available with one-height side panels resting on the beam.

Accessories

Tip-up writing table on single base mod. T200.

Tip-up writing table for the backrest with anti-panic movement, slow and cushioned closing (Patent Pending). Top in HPL laminate in beech, oak or black finishes.

Foldaway tip-up writing tablet in black stratified HPL, with anti-panic movement.

Plywood low backrest panel painted in oak or beech finishes (positioned on the backrest lower part).

Wood under seat panel painted in oak or beech finishes.

Seat numbering and row identification element.

Perforated aeration cylinder for single-base armchair.

Electric power supply provision (socket on demand).

Optional system allowing armchairs to be moved away on wheels when unused (for straight row armchairs).

Tested according to European standards.