

### Technical features

Armchair for conference halls and auditoriums.

### Typologies

Mura is available in the standard version with closed back and seat aligned with the sides. Produced with floor-length sides or on beam, 30 cm wide. Available with both high and low backrest.

Installation on flat and sloping floors or on steps, in straight or curved rows (standard minimum radius 15 m).

Centre to centre distance from 53 to 56 cm.

### Seat and backrest

Seat with plywood structure, padding in flame-retardant, non-deformable polyurethane foam.

Backrest available in two heights with plywood internal structure, padding in flame-retardant, non-deformable expanded polyurethane.

CertiPUR® certified padding. Wooden components with low formaldehyde emission.

Armchair equipped with a gravity system which releases and tips up the seat with "soft-close" movement slowed by a damper. At the same time the seat drops and uprights, reducing the volume of the armchair and increasing the available space between rows with a considerable advantage for the audience access/exit and for the cleaning and maintenance operations.

### Side

30 cm-thick side, has plywood inner structure, with flame-retardant, expanded polyurethane foam padding. Covering with fabric, leather or faux-leather.

CertiPUR® certified padding. Wooden components with low formaldehyde emission.

On project, the sides can be 24 cm wide.

The side is foreseen for floor-fixing, with steel sheet foot painted with epoxy scratchproof and anti-corrosion powder in semi-matt black RAL 9005, semi-matt silver, embossed bronze and embossed graphite finishes.

The sides can be fitted with black stratified HPL tip-up writing tablet and die-cast aluminium joint, that folds away into the side with anti-panic movement.

### On beam version structure

Also available the beam (2 or 3 places) in tubular steel square section, painted with scratchproof and anti-corrosion epoxy powder paint in semi-matt black RAL 9005, semi-matt silver, embossed bronze or embossed graphite finish. Painted steel foot designed to be fixed to the floor every 2/3 seats.

In the beam-mounted version, the sides have the same characteristics but are available with one height side panels resting on the beam (with the exception of the starting row sides that can even reach the ground).

## Accessories

Foldaway tip-up writing tablet with anti-panic movement (for 30-cm. thick side).

Seat and row identification elements.

Electrification provision (socket on demand).

Optional system allowing armchairs to be moved away on wheels when unused (for armchairs with floor-fixing feet in straight rows).

Tested according to European standards.