

Technical features

Armchair for conference halls and auditoriums.

Typologies

High or low backrest armchair with floor-length sides, set up for floor fixing.

Installation on horizontal and inclined floors or on steps, in straight or curved rows.

Variable centre-to-centre distance cm. 52, 56, 58 or 60.

Seat and backrest

Seat and backrest with steel tubular internal structure, fire-retardant cold-foamed expanded polyurethane padding provided with high-resistance elastic belts.

Leather, eco-leather or fabric upholstery.

Gravity tip-up seat, with rotation pins welded to the internal metal structure.

Backrest available in two heights.

A painted wood panel with oak or beech finishes can be applied onto the backrest lower part.

Seat and backrest inclination for stall or gallery.

Sides

Load-bearing side with steel tube internal structure hidden into a plywood box, available fully upholstered and covered, or in visible wood painted in oak or beech finishes.

Steel bearing inner structure, fitted with housings for the backrest pins and an aluminium block designed for the insertion of rotation and seat support pins.

Sides can be fully upholstered and covered or in painted wood with oak or beech finishes.

An added armrest, available in several versions, can be applied: in black RAL 9005 integral polyurethane, upholstered and covered or in wood (with oak or beech finishes).

For the version with added armrest, the right side is also available with tip-up anti-panic Medium Density writing tablet with black scratchproof PVC finish, which folds away into the side.

Foot equipped with a moulded sheet metal floor-fixing plate covered by a protective collar painted in semi-matt black RAL 9005, semi-matt silver or embossed graphite finishes.

Accessories

Foldaway tip-up writing tablet in Medium Density with black, scratchproof PVC finish, with anti-panic movement (only for the version with added armrest).

Painted plywood low backrest panel with oak or beech finishes (positioned onto the lower part of the backrest).

Painted plywood under seat panel with oak or beech finishes.

Row identification and seat numbering element.

Electrification provision, socket on demand (7 cm. side minimum width in case of electrification).

Accessory system allowing armchairs to be moved away on castors when not in use.

Tip-up writing tablet on single-base mod T200.

Tested according to European standards.